



VpCI™ FORMULATED PRODUCTS FOR PROCESS INDUSTRIES

VpCI™ -705 Bio Additive for Bio-fuels



Without VpCI-705 Bio



**Fuel treated
with VpCI-705 Bio**

PRODUCT DESCRIPTION

VpCI-705 Bio is specially formulated for use as a multifunctional fuel additive to biodiesel and other bio-fuels. It serves as a corrosion inhibitor, fuel stabilizer, and water emulsifier for biodiesel, diesel, and gasoline. VpCI-705 Bio provides corrosion protection, lubricity and elastomer protection for biobased fuels. As a fuel stabilizer, this product provides better engine performance.

VpCI-705 Bio provides excellent corrosion protection for all of the common engineering metals used in automotive fuel systems including aluminum, aluminum die cast and zinc die cast alloys, tinplate, copper, ferrous alloys, cast iron and solder. VpCI-705 Bio gives unique multimetal corrosion protection in all phases: liquid, interface and vapor phases above and below the fuel level.

TYPICAL APPLICATIONS

- Fuel tanks
- Carburetors
- Fuel pumps
- Upper engine cylinder components

ADVANTAGES

- Environmentally friendly
- Biobased product
- May be used in operation or storage
- Provides efficient corrosion protection in biodiesel, diesel, and gasoline
- Protects all metals including tinplate, terneplate, solder, copper, aluminum, steel and brass
- Protects upper cylinder walls, piston heads and rings during shutdown

- Provides protection in liquid and vapor phase and at liquid/air interface
- Passes Rust test in accordance to MIL-I-25017
- Passes Rust test in accordance to ASTM D665-92
- Liquid, easy to blend
- Fuel stabilizer allows better engine performance
- Does not contain trace metals, chlorides, chromates, nitrites or phosphates
- Does not form corrosive combustible products
- Absorbs water in tank and fuel line
- Can be fogged into fuel tanks

APPLICATION

In-use fuel tanks:

Add VpCI-705 Bio to biodiesel, gasoline and diesel fuel, fuel blending and storage facilities or directly to fuel tanks.

Dosage: 0.1 - 0.2% per volume.

Storage and shipment of dry fuel tanks:

Fog VpCI-705 Bio into tank, covering as much internal surface area as possible.

Dosage: 1.5 oz. per 10 U.S. gallons tank volume (45 ml per 37 liters of tank volume.)

PHYSICAL PROPERTIES

Appearance	Clear amber liquid
Density	7.3-7.6 lb/gal (0.87-0.91 kg/l)
Odor	Vegetable oil-like
Non-volatile Content	94-98%
Coverage	770-790 ft ² /gal (18-19 m ² /l)
Flash Point	316°F (158°C)

PACKAGING

VpCI-705 Bio is available in 5 gallon (19 liter) pails, 55 gallon (208 liter) drums, liquid totes and bulk.



FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.


BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.cortecvci.com>

printed on recycled paper  100% post consumer

Revised 5/29/08. Cortec Corporation 2004-2008. All rights reserved. Supersedes: 4/21/04.
VpCI® is a trademark of Cortec Corporation. © 2008, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited.