

VpCI™ METALWORKING PRODUCTS

EcoLine® Heavy Duty Grease



PRODUCT DESCRIPTION

EcoLine Heavy Duty Grease is formulated with American-grown natural seed oil that surpasses the lubricity of most conventional petroleum based greases. Utilizing the latest biotechnology, EcoLine Heavy Duty Grease is an environmentally friendly replacement for harmful greases.

In addition to lubricating, self-healing, and moisture displacing properties this biodegradable grease provides a powerful combination of contact and vapor phase corrosion protection. EcoLine Heavy Duty Grease can protect bearings and other equipment from corrosion during operation and lay-up without harming the environment.

FEATURES

- Provides superior lubricity to promote longer equipment life
- Clay-based thickener resists drop in viscosity at high-temperatures
- Superior adhesion and resists water wash out
- Excellent outdoor protection against corrosion caused by chlorides, acids, and other corrosive species
- Provides contact and vapor phase protection
- Selfhealing

- High viscosity index at wide temperature ranges
- Biodegradable when released into the environment
- High flash and fire points reduce fire hazards
- Meets EPA's Environmental Preferable Purchasing criteria
- Meets USDA's Biobased product definition for EO 13101

TYPICAL APPLICATIONS

- For applications where long-term corrosion protection and lubrication is required
- Gear protectant / lubricant
- Outdoor long-term corrosion inhibitor/coating
- Long-term equipment lay-up

TYPICAL PROPERTIES

NLGI Grade No.	2
Thickener	Clay
Appearance	Red Grease
Cone Penetration, Worked 60 Strokes	285
Non-volatile content	95-99.9%
Density	7.3-7.6 lb/gal (0.86-0.91 kg/l)
Protection in Salt Spray Cabinet (ASTM B-117) Carbon Steel Film Thickness 3-mil	500 hours
Weld Load (Kg)	250
Base Oil, Viscosity, cSt at 40C	40
Base oil, Flash Point	619°F (326°C)
Base Oil, Pour Point	18°F (-8°C)
Base Oil Biodegradability	Pass
Base Oil Aquatic Toxicity	Non-toxic

METALS PROTECTED

- Carbon Steel
- Stainless Steel
- Cast iron
- Aluminum and alloys
- Copper and alloys

APPLICATION

Product Preparation:

Product should be mixed thoroughly and uniformly prior to use.

Product Application:

Product can be applied by brush or roll. Normal DFT is 2 mils (50 microns).

Product Cleanup:

For cleanup of tools and overspray, use alkaline cleaners such as Cortec VpCI-414 or mineral spirits.

PACKAGING AND STORAGE

EcoLine Heavy Duty Grease is available in 5 gallon (19 liter) plastic containers, 55 gallon (208 liter) metal drums, and 16 oz. (454 g) cartridges. Store in cool dry warehouse.

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

KEEP CONTAINER TIGHTLY CLOSED

NOT FOR INTERNAL CONSUMPTION

CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@cortecvci.com
Internet <http://www.CortecVCI.com>

printed on recycled paper  100% post consumer
Revised 4/8/08. ©Cortec Corporation 2002-2008. All rights reserved. Supersedes: 5/1/06.
Cortec®, and EcoLine® are trademarks of Cortec Corporation.
© 2002-2008, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited.